



Eggshell Finish
Product No. 02770
Satin Finish
Product No. 02700
Semi-Gloss Finish
Product No. 02750

Perma-White[®] Mold & Mildew-Proof[™] Interior Paint

Perma-White is a high performance acrylic interior paint formulated to beautify and protect interior surfaces while preventing mold & mildew growth on the paint film for FIVE YEARS. Perma-White passes severe ASTM D5590 and D3273 tests even when subjected to combined strains of mold & mildew spores. Perma-White produces a beautiful, tough, durable, washable finish that withstands moisture and resists dirt pickup – key conditions that promote mold & mildew growth on the paint film and eventually cause paint failure. Ideal for commercial, industrial, residential or IAQ remediation jobs.

- Mold & Mildew-Proof[™] paint film guaranteed for 5 years
- Durable, beautiful long lasting finish
- Antimicrobial – inhibits the growth of odor causing microbes on the paint film (does not protect against food borne or disease-causing bacteria).
- Self-priming – bonds to glossy and hard-to-paint surfaces
- Easy application, high hide, great touch-up
- Washable/scrubbable, moisture and stain resistant finish
- Low VOC, low odor, fast drying – recoat in 2 hours
- Soap and water cleanup
- Tintable to a wide variety of colors

*This product contains a mildewcide to prevent the growth of mold & mildew on the paint film only.

Generic Type

Water-base, acrylic latex interior paint with a proprietary resin system and mildewcide package.

Surfaces

May be applied to any paintable interior surface including walls, wall cavities, ceilings, paneling, trim, doors, cabinets, etc.

Substrates

New or previously painted interior drywall, cured plaster and masonry (including stucco, concrete block, poured concrete and brick); wood (including pine, plywood, T1-11, particleboard, etc); primed or previously painted metal (including aluminum, steel and galvanized metal); rigid, paintable plastics; glossy surfaces (tile, Formica[®], glass).

Spread Rate

A single coat covers approx. 400 sq. ft. (37 m²) per gallon @ 1.5 mil DFT. Coverage will vary with the porosity of the surface and method of application.

Application Methods: **Brush, roller, sprayer**

Sheen @ 60°: **5-8% Eggshell (E)**
18-23% Satin (S)
50-55% Semi-Gloss(SG)

Solids by Weight: **57%(E), 54%(S), 51% (SG)**

Solids by Volume: **41%(E), 38%(S), 38% (SG)**

MAX VOC: **50 g/L**

Dry to Touch @ 70°F: **30 minutes**

Dry to Recoat @ 70°F: **2 hours**

Application Conditions

Humidity: **10% to 80%**

Temp: **50°F to 90°F**

Cleanup: **Water and detergent**

Availability: **Qt, Gal, 5-Gal**

Limitations: Not intended for application to floors or surfaces subject to water immersion or prolonged contact with water including shower enclosures, saunas or steam rooms. Not recommended for use in HVAC ductwork.

ASTM D5590

Determining the resistance of paint films and related coatings to fungal defacement by accelerating four-week agar plate assay

Perma-white paint film shows no indication of mold growth.



Competitive paint shows mold growth after four weeks.

